

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
23 August 2001 (23.08.2001)

PCT

(10) International Publication Number  
**WO 01/60954 A1**

- (51) International Patent Classification<sup>7</sup>: **C10L 1/02**
- (21) International Application Number: **PCT/NL00/00950**
- (22) International Filing Date:  
22 December 2000 (22.12.2000)
- (25) Filing Language: **Dutch**
- (26) Publication Language: **English**
- (30) Priority Data:  
1013964 27 December 1999 (27.12.1999) **NL**
- (71) Applicant (for all designated States except US): **PURAC BIOCHEM B.V.** [NL/NL]; Postbus 21, NL-4200 AA Gorinchem (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **NANNINGA, Gerrit, Leendert** [NL/NL]; Korenschoof 44, NL-4283 HH Giessen (NL). **VAN BREUGEL, Jan** [NL/NL]; Middelwaard 48, NL-4285 WS Woudrichem (NL).
- (54) Title: **FUEL COMPOSITION**
- (57) Abstract: The invention relates to a fuel composition which comprises a diesel fuel, a C<sub>1</sub>-C<sub>4</sub>-alkyl ester of an α-hydroxymono-carboxylic acid and, if appropriate, a C<sub>1</sub>-C<sub>4</sub> alcohol. The diesel fuel is either obtained from petroleum or from a petroleum fraction, such as a middle distillate, or is obtained by conversion of material of biological origin (so-called biodiesel). The fuel composition preferably contains from 3 to 6 % by weight C<sub>1</sub>-C<sub>4</sub>-alkyl ester, calculated on the basis of the total weight of the composition.
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



**WO 01/60954 A1**

## Fuel composition

The invention relates to a fuel composition which comprises a diesel fuel, a C<sub>1</sub>-C<sub>4</sub>-alkyl ester of an  $\alpha$ -hydroxymonocarboxylic acid and, if appropriate, a C<sub>1</sub>-C<sub>4</sub>-alcohol. The diesel fuel is either obtained from petroleum or from a petroleum fraction, such as a middle distillate, or is obtained by conversion of material of biological origin (so-called biodiesel). The fuel composition is particularly suitable as a fuel for diesel engines. If the fuel composition comprises biodiesel, it is particularly suitable for use for simultaneously operating engines and heating devices, such as heaters on a ship.

10 Diesel fuels have to satisfy a number of specifications. According to ASTM D-975, it is possible to distinguish between three types of diesel fuel, namely 1-D for high-speed diesel engines which operate under greatly fluctuating conditions in terms of speed and load, 2-D, which is a general-purpose diesel fuel, and 4-D, which is a more viscous diesel fuel which is generally used in low-speed diesel engines. Low-speed diesel engines of this type generally run at a constant speed and under a constant load. One of the important specifications for diesel fuels is the flash point. The flash point represents the temperature below which a fuel can be handled without being at risk of catching fire. In other words, in connection with a possible fire risk, the flash point of the diesel fuel must not be too low. On the other hand, the flash point of the diesel fuel must not be too high, as in this case the diesel fuel is difficult or impossible to ignite, since at this temperature there are too few volatile components. The flash point is measured in accordance with ASTM D-93, and the flash point specifications for 1-D, 2-D and 4-D are 38°C, 52°C and 55°C, respectively: Kirk-Othmer, Encyclopedia of Chemical Technology, Fourth Edition, Volume 12, pp. 373-383 (1994).

25 It is known to add oxygen-containing compounds, such as esters of vegetable oils, ethers and alcohols, to diesel fuel in order to improve the combustion of the diesel fuel and to lower the emissions of carbon monoxide and particles. For example, ethanol could also be used to lower the flash point. However, ethanol has the considerable drawback of being a very volatile compound, the actual concentration of which in the diesel fuel is difficult to regulate and maintain at a constant level (ethanol has a boiling point of 78°C and a vapour pressure of 59 mbar at 20°C). Moreover, ethanol has a relatively low flash point and even a very small amount of ethanol is

sufficient to considerably lower the flash point: the addition of, for example, 1% by weight ethanol to a diesel fuel obtained from petroleum or a petroleum fraction leads to the flash point being lowered by approximately 25°C, which generally leads to a diesel fuel with an excessively low flash point. Ethanol as such is therefore unsuitable as an agent for lowering the flash point.

Various diesel fuels can be used as the base material for the fuel composition. The diesel fuel may be produced from a petroleum or a petroleum fraction, but is preferably produced by conversion of material of biological origin (so-called biodiesel).

Biodiesels with various flash points are used. However, the flash point of most biodiesels is too high, and consequently they cannot be used for diesel fuel compositions with a low flash point, such as those of type 1-D and 2-D. The invention provides a solution to these problems.

It has now been found that C<sub>1</sub>-C<sub>4</sub>-alkyl esters of  $\alpha$ -hydroxymonocarboxylic acids are very suitable agents for lowering the flash point of diesel fuels, in particular of biodiesels. Examples of esters of this type are the methyl, ethyl, n-propyl, i-propyl, n-butyl, s-butyl, i-butyl and t-butylesters of carboxylic acids, such as lactic acid. The ester is preferably ethyl lactate (boiling point 154°C, vapour pressure at 20°C is 2.2 mbar). A further advantage is that the addition of these esters increases the oxygen content thereby providing an improved combustion and less soot formation.

According to the invention, the fuel composition also contains a C<sub>1</sub>-C<sub>4</sub>-alcohol. Examples of an alcohol of this type include methyl alcohol, ethyl alcohol, n-propyl alcohol, i-propyl alcohol, n-butyl alcohol, s-butyl alcohol, i-butyl alcohol and t-butyl alcohol. The alcohol is preferably ethanol.

The fuel composition preferably comprises from 3 to 6% by weight, in particular 4 to 5% by weight, C<sub>1</sub>-C<sub>4</sub>-alkyl ester, calculated on the basis of the total weight of diesel fuel and alcohol. If present, the fuel composition preferably also contains from 0.05 to 1.0% by weight, in particular 0.1 to 0.5% by weight, C<sub>1</sub>-C<sub>4</sub>-alcohol, calculated on the basis of the total weight of diesel fuel, ester and alcohol. It has been found that it is advantageous for the fuel composition to contain both the ester and the alcohol, since at ambient temperature all the components (diesel fuel, alcohol and ester) in any ratio produce a completely homogeneous fuel composition with a pour point which is lower than 0°C and often even lower than -4°C. Moreover, it has been

found that the effect of the alcohol, in particular of ethanol, of considerably reducing the flash point can be lessened by the addition of the ester.

The fuel composition preferably also contains one or more fatty acids for stabilising the flash point. It has been found that the following fatty acid composition is

5 eminently suitable:

free fatty acid content: approximately 80% by weight

fatty acid derivatives: approximately 20% by weight

fatty acid composition: 0.1% by weight C14:0, 6% by weight C16:0  
10 (palmitic acid), 0.4 % by weight C16:1, 0.2% by weight C18:0, 57% by  
weight C18:1 (oleic acid), 22% by weight C18:2 (linoleic acid), 7% by  
weight C18:3 (linolenic acid) and 0.2% by weight C22:1.

The fuel composition may furthermore contain the customary additives,  
such as agents which improve the cetane number, agents which improve the cold filter  
plugging point, ignition-promoting agents, agents which improve the pour point,  
15 detergents and rust-preventing agents.

If the ester is used for lowering the flash point of fuels (for example diesel  
fuel) which have been prepared from petroleum or petroleum fractions such as middle  
distillates, this may lead to two-phase systems being formed. This occurs, for example,  
if approximately 3% by weight of the ester (calculated on the basis of the total fuel  
20 composition) is added to the diesel fuel. By contrast, the formation of two-phase  
systems can be counteracted again by also adding a fatty acid or a mixture of fatty  
acids. The quantities of ester, alcohol and fatty acid or fatty acids which have to be  
added to fuels of this type in order to suitably lower the flash point lie within the same  
ranges.

25

#### Example 1

Fuel compositions containing the following components were prepared, and  
the flash point of these compositions was determined in accordance with the method  
described in ASTM D-93 (ISL FP 93 5G). The diesel fuel was obtained from Shell (8  
30 November 1999, 08.14 h, Giessen, The Netherlands). The specifications of the diesel  
fuel were as follows:

- cloud point (seasonably dependent)
- cold filter plugging point (EN 116; seasonably dependent)

- cetane index (ASTM D-4737): minimum 46
- cetane number (ASTM D-613): minimum 49
- density (ASTM D-4052): 820-860 kg/dm<sup>3</sup>
- maximum boiling point (ASTM D-86): maximum 370°C
- 5 • flash point (ASTM D-93): minimum 55°C
- sulphur content (ASTM D-2622): maximum 0.05% by weight
- viscosity (ASTM D-445): minimum 2.0 mm<sup>2</sup>/S
- water content (ASTM E-1064): maximum 200 mg/l.

10       The fatty acid composition was obtained from Vogtrans (Fettsäure Typ I, 816+ 781, 10.4.99). The ethanol was obtained from Merck (absolute, for analysis). The ethyl lactate was obtained from Purac (batch HK 435 GL). The following results were obtained (cf. Table 1):

Table 1

	Fatty acids (% by weight)	Ethanol (% by weight)	Ethyl lactate (% by weight)	Flash point (°C)
1	0.00	0.00	0.00	50.6
2	0.00	0.00	1.25	48.6
3	0.00	0.00	2.50	47.6
4	0.00	1.25	0.00	17.6
5	0.00	1.25	1.25	18.6
6	0.00	1.25	2.50	20.6
7	0.00	2.50	0.00	12.5
8	0.00	2.50	1.25	14.5
9	0.00	2.50	2.50	15.5
10	2.50	0.00	0.00	51.6
11	2.50	0.00	1.25	50.6
12	2.50	0.00	2.50	47.6
13	2.50	1.25	0.00	18.5
14	2.50	1.25	1.25	20.5
15	2.50	1.25	2.50	22.5
16	2.50	2.50	0.00	15.5
17	2.50	2.50	1.25	16.5
18	2.50	2.50	2.50	16.5
19	5.00	0.00	0.00	52.6
20	5.00	0.00	1.25	50.6
21	5.00	0.00	2.50	49.6
22	5.00	1.25	0.00	20.5
23	5.00	1.25	1.25	22.5
24	5.00	1.25	2.50	24.5
25	5.00	2.50	0.00	16.5
26	5.00	2.50	1.25	17.5
27	5.00	2.50	2.50	19.5
28	2.50	1.25	1.25	20.5
29	2.50	1.25	1.25	20.5
30	2.50	1.25	1.25	20.5

It is clear from the above table that in practice it is not possible to lower the flash point using ethanol.

Calculations have shown that the increase in the flash point brought about by ethyl lactate (2.50% by weight) and the fatty acid compositions (5.00% by weight) is negated by the addition of 0.12% by weight ethanol. When more than approximately 3% by weight ethyl lactate was added, segregation occurred at ambient temperature, which again could be negated by the addition of the fatty acid composition.

### Example 2

Fuel compositions comprising the following components were prepared, and the flash point of these compositions was determined in accordance with the method described in ASTM D-93 (ISL FP 93 5G). The biodiesel was obtained from Q8 (KPA 2536, Biodiesel/RME, RL98-1719). The fatty acid composition was obtained from Vogtrans (Fettsäure Typ I, 816 + 781, 10.4.99). The ethanol was obtained from Merck (absolute, for analysis). The ethyl lactate was obtained from Purac (batch HK 435 GL). The following results were obtained (cf. table 2):

It emerged that, when ethanol and/or ethyl lactate was added, no segregation occurred, and consequently the addition of the fatty acid composition is not strictly necessary. The flash point can be lowered by adding ethyl lactate alone, although approximately 12% by weight ethyl lactate then has to be added in order to reduce the flash point from 170°C to 70°C, which is not attractive from an economic point of view. This has the further drawback that the efficiency of combustion is reduced by approximately 6%. For practical reasons, according to the invention the flash point is preferably lowered by adding a mixture of ethanol and ethyl lactate.

ASPEN calculations have shown that ethyl lactate lowers the pour point of the fuel (if methyl oleate is the fuel, adding 10% by weight ethyl lactate lowers the pour point from 7.67°C to -0.18°C), which is an additional advantage since less pour point depressant has to be added.

Table 2

	Fatty acids (% by weight)	Ethanol (% by weight)	Ethyl lactate (% by weight)	Flash point (°C)
1	1.03	0.99	3.19	44.9
2	2.02	0.98	3.19	45.9
3	1.03	1.95	3.22	31.9
4	1.99	1.94	3.16	33.0
5	1.02	0.96	6.14	46.0
6	1.96	0.96	6.12	47.0
7	1.02	1.87	6.04	35.0
8	1.98	1.87	6.01	35.0
9	2.01	1.81	5.09	34.5
10	2.09	0.55	5.21	54.5
11	1.69	1.43	4.68	39.0
12	1.68	1.43	4.61	40.0
13	0.00	0.00	6.24	85.0
14	0.00	1.54	0.00	34.2
15	2.33	0.00	0.00	181.0
16	0.00	0.00	0.00	176.0
17	0.00	1.00	3.90	48.2
18	0.00	0.51	3.91	59.0
19	0.00	0.52	0.00	34.2
20	0.56	0.53	3.90	59.0
21	0.93	0.51	3.96	47.0
22	0.00	0.32	1.38	67.0
23	0.00	0.49	2.63	63.0
24	0.66	0.60	1.90	56.0
25	0.94	1.00	1.11	36.8
26	1.01	1.00	0.00	54.8
27	1.05	0.00	1.13	124.8
28	0.00	0.00	0.00	176.8
29	0.00	0.00	3.24	97.8
30	0.00	0.00	6.35	81.8



31	0.00	0.27	0.00	101.8
32	0.00	0.26	3.27	78.8
33	0.00	0.25	6.38	67.8
34	0.00	0.53	0.00	77.8
35	0.00	0.51	3.29	63.8
36	0.00	0.50	6.39	57.8
37	0.00	0.26	3.22	77.8
38	0.00	0.26	3.21	76.8
39	0.00	0.00	3.28	96.8
40	0.00	0.53	0.00	62.8
41	0.00	0.53	0.00	72.8
42	0.00	0.53	0.00	67.8
43	0.00	1.05	0.00	42.8
44	0.00	1.03	3.22	43.8
45	0.00	0.98	6.13	46.8
46	0.00	0.00	11.84	70.8
47	0.00	0.94	11.99	50.7
48	0.00	0.78	0.00	48.12
49	0.00	0.77	3.18	49.1
50	0.00	0.69	9.22	52.1
51	0.00	0.73	6.46	50.2
52	0.00	0.87	3.21	46.2
53	0.00	0.39	5.13	61.2
54	0.00	0.41	3.87	62.2
55	0.00	0.31	3.21	68.2
56	0.00	0.49	2.62	59.2
57	0.00	0.99	2.94	43.2

CLAIMS

1. Fuel composition comprising a diesel fuel and a C<sub>1</sub>-C<sub>4</sub>-alkyl ester of an  $\alpha$ -hydroxymonocarboxylic acid.
- 5 2. Fuel composition according to Claim 1, in which the diesel fuel is biodiesel.
3. Fuel composition according to Claim 1 or 2, which comprises a C<sub>1</sub>-C<sub>4</sub>-alcohol.
4. Fuel composition according to one of the preceding claims, in which the  $\alpha$ -  
10 hydroxymonocarboxylic acid is lactic acid.
5. Fuel composition according to one of the preceding claims, in which the C<sub>1</sub>-C<sub>4</sub>-alkyl ester of the  $\alpha$ -hydroxymonocarboxylic acid is ethyl lactate.
6. Fuel composition according to one of the preceding claims, in which the C<sub>1</sub>-C<sub>4</sub>-alcohol is ethanol.
- 15 7. Fuel composition according to one of the preceding claims, which contains from 3 to 6 % by weight C<sub>1</sub>-C<sub>4</sub> alkyl ester, calculated on the basis of the total weight of the composition.
8. Fuel composition according to one of the preceding claims, which contains from 4 to 5 % by weight C<sub>1</sub>-C<sub>4</sub> alkyl ester, calculated on the basis of the total weight of  
20 the composition.
9. Fuel composition according to one of the preceding claims, which contains from 3 to 6 % by weight C<sub>1</sub>-C<sub>4</sub> alkyl ester and 0.05 to 1.0% by weight C<sub>1</sub>-C<sub>4</sub> alcohol, calculated on the basis of the total weight of the composition.
10. Fuel composition according to one of the preceding claims, which contains  
25 from 4 to 5 % by weight C<sub>1</sub>-C<sub>4</sub> alkyl ester and 0.1 to 0.5% by weight C<sub>1</sub>-C<sub>4</sub> alcohol, calculated on the basis of the total weight of the composition.
11. Use of a C<sub>1</sub>-C<sub>4</sub>-alkyl ester of an  $\alpha$ -hydroxymonocarboxylic acid for lowering the flash point of a fuel composition.
12. Use of a C<sub>1</sub>-C<sub>4</sub>-alkyl ester of an  $\alpha$ -hydroxymonocarboxylic acid for  
30 lowering the pour point of a fuel composition.
13. Use according to Claim 11 or 12, in which the fuel composition comprises a biodiesel.

14. Use according to Claim 11 or 12, in which the fuel comprises a diesel fuel which has been prepared from middle distillates.
15. Use according to one of Claims 11-14, in which the ester is ethyl lactate.

# INTERNATIONAL SEARCH REPORT

Int:      onal Application No  
PCT/NL 00/00950

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C10L1/02

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C10L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 1 525 804 A (SHELL INT RESEARCH) 20 September 1978 (1978-09-20) the whole document ---	1,2,4,14
A	WO 95 02654 A (VICTORIAN CHEMICAL INTERNATION ;KILICK ROBERT WILLIAM (AU); WRIGL) 26 January 1995 (1995-01-26) claims 1-3,7,11 page 3, line 1 - line 17 ---	1-3,6-10
A	US 4 762 946 A (RITTER WOLFGANG ET AL) 9 August 1988 (1988-08-09) claims 1,3,4 -----	1,2,4,12

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the International filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*G\* document member of the same patent family

Date of the actual completion of the international search

13 May 2001

Date of mailing of the international search report

21/05/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

De Herdt, O

# INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/NL 00/00950

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 1525804 A	20-09-1978	DE 2711218 A	29-09-1977
		DK 113277 A	18-09-1977
		FR 2344625 A	14-10-1977
		NO 770924 A	20-09-1977
		SE 7702943 A	18-09-1977
WO 9502654 A	26-01-1995	AT 181353 T	15-07-1999
		AU 676930 B	27-03-1997
		AU 7223194 A	13-02-1995
		BR 9407052 A	13-08-1996
		CA 2167294 A	26-01-1995
		DE 69419155 D	22-07-1999
		DE 69419155 T	18-11-1999
		EP 0708808 A	01-05-1996
		US 6129773 A	10-10-2000
US 4762946 A	09-08-1988	DE 3513356 A	16-10-1986
		US 4906702 A	06-03-1990

## WO0160954

Publication Title:

Fuel composition

Abstract:

The invention relates to a fuel composition which comprises a diesel fuel, a C1-C4-alkyl ester of an alpha-hydroxymonocarboxylic acid and, if appropriate a C1-C4-alcohol. The diesel fuel is either obtained from petroleum or from a petroleum fraction, such as a middle distillate, or is obtained by conversion of material of biological origin (so-called biodiesel). The fuel composition preferably contains from 3 to 6% by weight C1-C4-alkyl ester, calculated on the basis of the total weight of the composition.

-----  
Data supplied from the esp@cenet database - <http://ep.espacenet.com>